



Your Best Protection Against Burglary and Fire

PINGAN is committed to providing customers with a fully secure unit, boasting a sleek and modern look which blends seamlessly into any interior design scheme. Finished with polished stainless steel or powder coating, this safe reflects a strong yet elegant image.

Features:

- Cost effective solution for confidential / sensitive documents and data storage
- 3-way block and relock mechanism
- Closed position of hinges designed to prevent forced entry
- Fire resistant up to 1 hour (Class B)

Options:












- 3-Wheel Mechanical Lock
- Electronic Motor Lock by Fingerprint / Pin code / One-Time-Combination
- Time Lock



FDG-B2/J-168



FDG-B2/J-138

Model	 Width (mm)	 Depth (mm)	 Height (mm)	 Width (mm)	 Depth (mm)	 Height (mm)	 Kg	 Lock	 Key	 120 mins	 Shelf	Body Thickness (mm)	Door Thickness (mm)
FDG-B2/J-87	550	500	870	379	279	699	298	1	2	165	2	85	127
FDG-B2/J-114	613	512	1140	442	291	969	402	1	2	165	3	85	127
FDG-B2/J-138	630	620	1380	459	399	1209	830	1	2	165	3	85	127
FDG-B2/J-168	694	720	1676	523	500	1505	1050	1	2	165	4	85	127



FDG-A2/J-56P



FDG-A2/J-70P













FDG-A2/J-87P



FDG-A2/J-114P



FDG-A2/J-138P

Model	 Width (mm)	 Depth (mm)	 Height (mm)	 Width (mm)	 Depth (mm)	 Height (mm)	 Kg	 Lock	 Key	 Shelf
FDG-A2/J-56	420	400	560	357	286	499	134	1	2	1
FDG-A2/J-70	550	500	700	470	367	620	251	1	2	1
FDG-A2/J-87	550	500	870	470	367	790	298	1	2	2
FDG-A2/J-114	613	512	1140	533	379	1060	402	1	2	3
FDG-A2/J-138	613	512	1380	533	379	1300	570	1	2	3



BURGLARY & FIRE RESISTANT SAFE

PA offers various styles and dimension combination to satisfy different customers' needs. In addition, all our safe deposit boxes are precisely crafted to offer a homogenous appearance when stacked together.

SECURITY



UL CERTIFIED SAFE

Pingan safes are UL certified to provide burglary resistance of up to 30 minutes on all 6 sides for our TL30x6 models.



RELOCKING SYSTEM

3 way boltwork will activate automatically when it senses any burglary attempts for additional safety.



ULTRA HIGH STRENGTH BUILT

Up to 10 mm of ultra high strength quality steel with patented extra strong filling materials are used to built the safes. This is the most rigorously built safe when compared to others in its class.



DUAL KEY LOCK

For additional protection, all Pingan safe is equipped with dual lock. One primary lock (that can be chosen between UL listed mechanical lock or electronic lock) and one secondary key lock.

Customisation: Safes can be customised with a selection of newly designed opening handles, colors and selection of various type of UL certified primary locks, mechanical locks or high security electronic locks. We can also tailor made to the required size should you need dimensions that is different from our current models.

Design: In addition to providing best in class protection, our contemporary yet practical design will fit harmoniously with your interior decor.

Alarm: Provision for all safes to be fitted with an electronic alarm system that match your specific needs and increase even more the protection of your valuables.

Floor anchorage: Provision for all safes to be anchored onto the floor to resist forced removal.

OPTIONS

LOCK



Combination lock



OTC

COLOURS



Charcoal Grey



Cream White

SECURITY



LISTED



UL TL-15 X 6

UL TL-15 X 6 RATED SAFE: A TL-15 means an expert safebreaker will need 15 min to access the safe. All 6 sides including door have the same level of burglary resistance.



UL TL-30 X 6

UL TL-30 X 6 RATED SAFE: A TL-30 means an expert safebreaker will need 30 min to access the safe. All 6 sides including door have the same level of burglary resistance.

TECHNICAL INFORMATION

MODELS



UL TL-15X6 certified

UL-TL15x6-70P	630	620	700	456	393	526	570	1	2	1
UL-TL15x6-90P	630	620	900	456	393	726	710	1	2	2
UL-TL15x6-115P	630	620	1150	456	393	976	870	1	2	3
UL-TL15x6-138P	630	620	1380	456	393	1206	1040	1	2	3
UL-TL15x6-168P	694	720	1676	520	493	1502	1460	1	2	4

UL TL-30X6 certified

UL-TL30x6-70P	630	620	700	456	393	526	510	1	2	1
UL-TL30x6-90P	630	620	900	456	393	726	630	1	2	2
UL-TL30x6-115P	630	620	1150	456	393	976	780	1	2	3
UL-TL30x6-138P	630	620	1380	456	393	1206	930	1	2	3
UL-TL30x6-168P	694	720	1676	520	493	1502	1300	1	2	4

REGALIA Safe



Size 1



Size 3



Size 2



Size 4



Size 5

	External (mm / inches)			Internal (mm / inches)										
Model	Height	Width	Depth	Height	Width	Depth	Adjustable shelf	Drawer	Drawer Height	Nett Weight (kg)	Capacity (litre)	Front Bolt	Back Bolt	Top + Bottom Bolt
Super Sub 1	400 / 15.7"	510 / 20.0"	530 / 20.9"	260 / 10.2"	370 / 14.5"	328 / 12.9"	1	0	0	185	31.5	2	dogging	1 + 1
Super Sub 2	510 / 20.0"	460 / 18.2"	530 / 20.9"	370 / 14.5"	315 / 12.4"	328 / 12.9"	1	0	0	200	38.2	2	dogging	1 + 1
Super Sub 3	600 / 23.6"	510 / 20.0"	530 / 20.9"	450 / 17.7"	370 / 14.5"	328 / 12.9"	1	1	101 / 4.0"	235	54.6	3	dogging	1 + 1
Super Sub 4	760 / 30.0"	510 / 20.0"	530 / 20.9"	610 / 24.0"	370 / 14.5"	328 / 12.9"	1	1	101 / 4.0"	305	74.0	3	dogging	1 + 1
Super Sub 5	1040 / 41.0"	610 / 24.0"	610 / 24.0"	885 / 34.8"	465 / 18.3"	420 / 16.5"	1	1	101 / 4.0"	500	172.8	4	dogging	1 + 1

Regalia Safe - *Super Sub* - is a Compact Series security safe ideally designed to protect valuables and important documents for home, office and retail shop against burglary and fire. It is equipped with:

- 70mm / 2.7" thickness of the body,
- 52mm / 2.0" thickness of door with effective of 110mm / 4.3",
- 4 to 6 pieces of 25mm / 1" diameter bolts.
- And our specially design locking mechanism.

The safe also have an option to secure by branded and reliable multi-function digital lock for easy to use.



SUPER SUB

EUROLITE PRO SAFES - S2, 30-P SERIES












Features

- Tested and Certified by CNPP - France & ECB.S - Germany, as per EN14450: S2 standards
- Light weight construction designed for Home & High rise installation
- A 3-way sturdy bolt-work & locking mechanism protected by special Drill Resistant plates
- Fire Resistant for 30 minutes - Tested and certified as per LFS 15659 - 30P standards
- Two Base or Rear Fixings - tested to 30KN pull force; ensures secure anchoring of the safe
- Fitted with an EN 1300 certified double bitted Key lock as standard. Options for Electronic Lock.
- Overnight Cash Cover - €20,000

(The above cash cover rating is recommended rating for Private Sector use. The recommended cover for Jewellery will be usually 10 times the However, these are indicative overnight cash & Jewellery covers only and may vary across geographical locations, depending on statutory compliance requirements and local laws. Insurers may assign different values to the one recommended above)

* The VDMA 24992 Class A & B specification standards have been officially withdrawn w.e.f 31st December, 2003

MODEL	PRO 40W	PRO 45	PRO 65	PRO 85	FS 150
E 	375	505	695	895	1150
X 	523	523	523	523	523
T 	470	470	470	470	470
I 	225	385	575	775	1030
N 	403	403	403	403	403
T 	310	310	310	310	310
Door at 90° (OD)	893	893	893	893	893
Door Swing Radius (S)	423	423	423	423	423
 in (Ltrs)	32	48	72	97	129
 Kg	65	80	102	124	152
Product Rating	Tested & Certified by CNPP - France & ECB.S - Germany				
Burglary Resistance	EN 14450: S2				
Fire Resistance	LFS 15659 :30P				
Std. Hanging of Door	Right Hung				
	1	1	2	2	3
Std. Locking **	1 No. EN 1300 Class A, Double Bitted Key Lock.				

* Tolerances on Weight - +/- 10%

* Model FS 10 is certified by LPCB - UK as per EN14450:S2 standards

